

One Stop Solution for Construction Material Needs

Export Product Catalogue

Steel Tube and Metal Decking | Galvanized roof and pipe | Drilling screws



SM. I. Roof Frames

01. C Truss





Size: 76 x 36 mm

Thickness: 0.55 - 1.00 mm

Length: 6 m

Lead Time Production: 2 – 4 weeks

* Custom Size Is Also Available With Minimum Quantity

02. Batten Hat





Size: 28 x 17 cm & 32 x 18 mm

Thickness: 0.45 mm

Length: 6 m

SM. II. Ceiling Frames

01. Furring





Size: 45 x 19 mm

Thickness: 0.35 - 0.40 mm

Length: 4 m

Lead Time Production: 2 – 4 weeks

* Custom Size Is Also Available With Minimum Quantity

02. Mini Runner






Size: 35 x 15 mm

Thickness: 0.35 - 0.40 mm

Length: 4 m

03. Hollow





Size: 20 x 40 mm & 40 x 40 mm Thickness: 0.25 – 0.55 mm


Length: 4 m

Lead Time Production: 2 – 4 weeks

* Custom Size Is Also Available With Minimum Quantity

04. Elbow








SM. III. Partition Frames

01. Metal Stud





Size: 51 x 33 mm & 76 x33 mm Thickness: 0.35 – 0.45 mm

Length: 3 m

Lead Time Production: 2 – 4 weeks

* Custom Size Is Also Available With Minimum Quantity

02. Metal Runner





Size: 51 x 20 mm & 76 x 20 mm Thickness: 0.35 – 0.45 mm

Length: 3 m





SM. IV. Galvanized Roof

01. Galvanized Roof



Galvanized roof is based on finest zinc coated steel that has corrosion resistance then formed with high technology roll-former machine. Therefore, it would not scratch the raw materials. It has precise and strong profile yet still esthetic for building.

Size: 750 mm

Thickness: 0.25 - 0.40 mm

Length: 3 - 6 m

Lead Time Production: 2 – 4 weeks

* Custom Size Is Also Available With Minimum Quantity

SM. V. Galvanized Pipe

01. Galvanized Pipe



Galvanized Steel Pipe is zinc coated steel pipe that provides rust and corrosion resistance. It is commonly used for building construction, industrial machinery, and water systems. Our galvanized pipe has finest quality that meets several standards such as ASTM A53 from the U.S and SNI 0039:2013 from Indonesia.

Size: 1/2" - 8"

Thickness: SCH20 and SCH40

Length: 6 m

SM. VI. Drilling Screws

01. Drilling Screws



Size: 10 x 16 mm | 10 x 19 mm | 12 x 20 mm | 12 x 25 mm | 12 x 30 mm | 12 x 40 mm | 12 x 45 mm | 12 x 50 mm





^{*} Custom Model and Size is Also Available with Minimum Quantity.






Residentials







Hotels







Buildings







And Many Other Projects.

